

# Acryl-ite GP Plus

## APPLICATION GUIDE

### Preparation:

Surfaces to be treated must be dry, free from grease, oil, debris and previous sealers. Joints should be filled or topped up to the bottom of the chamfer with clean, kiln dried jointing sand.

### Coverage:

Block Paving and Clay Pavers 1.5—2.5m<sup>2</sup> per litre.  
Paving Slabs 2—4m<sup>2</sup>. If in doubt contact Blackjack Surface Technology Ltd on 0845 6769703.

### Application:

Stir thoroughly before use. Apply with a brush, roller, sprayer or squeegee depending on the paver type and surface condition. Ensure sand filled joints are fully flooded with Acryl-ite GP Plus. Work the sealant into the joints for maximum penetration. Ensure the surface is evenly coated and ensure that no sealer is allowed to puddle within the texture of any riven surfaces. Any pooling should be removed by sponge or roller before it dries.

Clean accidental spills and splashes immediately with a clean damp cloth.

### Curing:

Surface will dry in approx. 4 – 6 hours depending upon ambient weather conditions.

### Appearance:

Acryl-ite GP Plus appears milky white when wet, but will dry clear. We recommend the application of a trial area where the appearance of the treated surface is of particular importance and to test that the paving is sufficiently porous to absorb the solution evenly and without leaving a surface film.

### Safety:

Do not use in the presence of foodstuffs. Wear personal protective clothing, goggles and gloves. Keep out of the reach of children.

### Storage:

Store at a temperature range of 5°C—30°C. Protect from frost. Do not allow the product to freeze.

### Shelf Life:

18 months in unopened container. Once opened use within 6 months.

### Transport:

Not classified as hazardous for road transportation.

**Advice:**

If using Acryl-ite GP Plus for the first time, we strongly recommend that you call our helpline on 0845 6769703, for advice on how best to apply the product. Failure to fully understand the product may lead to results that are not as aesthetically pleasing as required.

Acrylite GP Plus cannot be used on any previously sealed surfaces.

Whilst Blackjack Surface Technology Ltd believe that the data contained herein is factual, the opinions expressed are those of experts (qualified or otherwise) regarding the results of tests. The data is not to be taken as a warranty or representation for which Blackjack Surface Technology Ltd assumes legal responsibility. This data is offered solely for your consideration, investigation and verification. Any use of this data must be determined by the user to be according to the applicable laws and regulations

Blackjack Surface Technology Ltd try to ensure any advice, recommendations or information we may give in product literature is accurate and correct. However, we have no control over the circumstances in which our products are used, hence our advice does not release end-users from the obligation to satisfy themselves by prior testing that the product/s is suitable for their specific application, and that the actual conditions of use are suitable.

Accordingly no responsibility can be accepted, or any warranty given by ourselves, our representatives, agents or distributors. Each end-user should always ensure that they have consulted our latest publications and that the relevant information concerning this material is communicated to all members of their organisation handling our products.

Blackjack Surface Technology Ltd.'s liability is for replacement of material proved to be defective only.