

Acryl-ite MCU Paving Sealer

APPLICATION GUIDELINES

Acryl-ite MCU is only for use with Block Paving and Clay Pavers and is not for use with any other form of paving.

Ensure sufficient material is purchased to cover the entire job.

Make sure the paving surface and jointing sand is completely dry and free from dirt.

Ensure that Acryl-ite MCU is only applied when there is no rain forecast within the next 12 hours.

Do not apply when temperature is below 3°C or above 30°C.

Apply to new laid paving after 8 weeks and refurbished paving after 2 weeks.

Remove any efflorescence or dirt before application.

Ensure paving is thoroughly swept and that no jointing sand remains in the chamfers of the blocks or on the block surface.

Apply to edges of paving with a Tampico Masonry brush.

Apply evenly to the main area using a medium pile roller at the rate of approx. 2M² per litre for the first coat and then 4M² per litre for the 2nd coat.

Acryl-ite MCU must be laid as a 2-coat system, except on clay pavers where only 1 coat is necessary and should be applied by watering can and squeegee.

A MINIMUM of 3 hours and a MAXIMUM of 24 hours should be left between the first and second coats.

Avoid walking on the sealed area for 3 hours after application and do not drive motor vehicles on the paving for at least 24 hours.

CONTAINS XYLENE.

ALWAYS WEAR PROTECTIVE GLOVES AND GOGGLES. NO SMOKING. WEAR A MASK IN CONFINED AREAS

Only coat an area in which you can easily finish that day. If a break is required cut in to a sand joint using a paint brush to avoid a striped effect.

WARNING

If using Acryl-ite MCU for the first time, we strongly recommend that you call our helpline on 0845 6769703, for advice on how best to apply the product. Failure to fully understand the product may lead to results that are not as aesthetically pleasing as required.

Once applied, Acryl-ite MCU is almost impossible to remove.